

Parameter	Value				
	UpanelS110.9S	UpanelS111.2S	UpanelS111.5S	UpanelS111.9S	UpanelS112.5S
Model	UpanelS110.9S	UpanelS111.2S	UpanelS111.5S	UpanelS111.9S	UpanelS112.5S
Pixel Pitch	0.95mm	1.27mm	1.58mm	1.906mm	2.5mm
LED Type	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD
Brightness	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>
Pixel Density	110,1068pixels/m <sup>2</sup>	62,0000pixels/m <sup>2</sup>	39,6550pixels/m <sup>2</sup>	275267pixels/m <sup>2</sup>	15,5000pixels/m <sup>2</sup>
Pixels Per Panel	640x360 pixels	480x270 pixels	384x216 pixels	320x180 pixels	120x135 pixels
Module Size	304.96mm×343.08mm	304.96mm×343.08mm	304.96mm×343.08mm	304.96mm×343.08mm	304.96mm×343.08mm
Panel Size	609.92mm×343.08mm ×65mm	609.92mm×343.08mm ×65mm	609.92mm×343.08mm ×65mm	609.92mm×343.08mm ×65mm	609.92mm×343.08mm ×65mm
Weight	7.5kg/panel	7.5kg/panel	7.5kg/panel	7.5kg/panel	7.5kg/panel
Maintenance	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
Ingress Protection	Rear IP40	Rear IP40	Rear IP40	Rear IP40	Rear IP40
Material	Die-cast Magnesium/ Aluminum	Die-cast Magnesium/ Aluminum	Die-cast Magnesium/ Aluminum	Die-cast Magnesium/ Aluminum	Die-cast Magnesium/ Aluminum
Color Temperature	2,000K-9,500K Adjustable	2,000K-9,500K Adjustable	2,000K-9,500K Adjustable	2,000K-9,500K Adjustable	2,000K-9,500K Adjustable
Horizontal Viewing Angle	160°	160°	160°	160°	160°
Vertical Viewing Angle	160°	160°	160°	160°	160°
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1
Input Power <Max>	161 W/panel	126 W/panel	130 W/panel	125 W/panel	130 W/panel
Input Power <Typical>	51 W/panel	75 W/panel	43 W/panel	75 W/panel	43 W/panel
Input Voltage	100~240 VAC	100~240 VAC	100~240 VAC	100~240 VAC	100~240 VAC
Refresh Rate	1920~3840 Hz	1920~3840 Hz	1920~3840 Hz	1920~3840 Hz	1920~3840 Hz
Video Frame Rate	50 & 60Hz	50 & 60Hz	50 & 60Hz	50 & 60Hz	50 & 60Hz
Input Power Frequency	50 & 60Hz	50 & 60Hz	50 & 60Hz	50 & 60Hz	50 & 60Hz
Operating Temperature/Humidity	-10°C ~ +40°C/ 10~80%RH	-10°C ~ +40°C/ 10~80%RH	-10°C ~ +40°C/ 10~80%RH	-10°C ~ +40°C/ 10~80%RH	-10°C ~ +40°C/ 10~80%RH
Storage Temperature/Humidity	-20°C ~ +60°C/ 10~85%RH	-20°C ~ +60°C/ 10~85%RH	-20°C ~ +60°C/ 10~85%RH	-20°C ~ +60°C/ 10~85%RH	-20°C ~ +60°C/ 10~85%RH